

## Description

Double sided adhesive transparent polyester film, also available with double sided covering as 4052D.

## Release Paper

White silicone coated PE paper on both sides, 120 g/m<sup>2</sup>; 4052D with white silicone coated paper 135 g/m<sup>2</sup> and 98 g/m<sup>2</sup>

## Adhesive

Solvent polyacrylate, permanent

## Area of use

Mounting film for self adhesive equipment of even surfaces

## Technical Data

<b>Thickness*</b> (without protective paper and adhesive)	12 micron
<b>Temperature resistance***</b>	Adhered to aluminium, -40° C to +150° C, no variation
<b>Adhesive power*</b> (FINAT TM 1, after 24h, stainless steel)	11 N/25 mm
<b>Shelf life**</b>	2 years
<b>Application temperature</b>	> +8° C

\* average    \*\* in original packaging, at 20° C and 50% relative humidity    \*\*\* normal climate of Central Europe

## Note

Surfaces to which the material will be applied must be thoroughly cleaned and free from dust, grease or any other contamination that could affect the adhesion of the material. Freshly lacquered or painted surfaces should be allowed to dry for at least three weeks and to completely cure. The compatibility of selected lacquers and paints should be tested by the user, prior to application of the material. Furthermore, the application information published by ORAFOL must be considered. The batch traceability according to ISO 9001 is possible on the basis of the roll number.

## IMPORTANT NOTICE

All ORABOND® products are subject to careful quality control throughout the manufacturing process and are warranted to be of merchantable quality and free from manufacturing defects. Published information concerning ORABOND® products is based upon research which the Company believes to be reliable although such information does not constitute a warranty. Because of the variety of uses of ORABOND® products and the continuing development of new applications, the purchaser should carefully consider the suitability and performance of the product for each intended use, and the purchaser shall assume all risks regarding such use. All specifications are subject to change without prior notice.

ORABOND® is a registered trademark of ORAFOL Europe GmbH